



**Universal Tool**  
*Air Tools for Industry*



## UT8784-5 4-1/2" & 5" 2.4 HP ANGLE GRINDER



### FEATURES & SPECIFICATIONS

- 2.4 HP governed motor for stall-free operation
- Capable of 4-1/2" & 5" wheels
- Alloy steel spiral gears with heavy duty bearings for added reliability
- "Rapid-adjust" guard allows rotational adjustment without tools
- Rotational rear-exhaust deflector reduces noise output and allows operator to adjust flow direction
- Compact design - reduced weight
- Spindle lock for rapid wheel change can be moved to right or left side of body
- Vibration damped side handle included
- Insulated composite handle over-mold increases operator comfort

Model #	Motor (hp)	Motor (Kw)	Max. Wheel Dia. (in)	Guard Type	Speed (rpm)	Exhaust	Spindle Size	Weight (lb)	Weight (kg)	Length (in)	Length (mm)	Air Inlet (npt)	Rec. Hose (id. in)	Air Cons. (cfm)	Avg. Air Cons. (cfm)
UT8784-5	2.40	1.79	5"	Rapid Adjust	12,000	Rear	5/8" - 11	3.90	1.77	9.80	248.92	3/8"	1/2	10	10.00

Recommended Air Pressure of 90 psi - 6.2 bar

See accessories on page 68