



Universal Tool
Air Tools for Industry



UT8789-5-336 **5" ORBITAL PALM SANDER**



FEATURES & SPECIFICATIONS

- Only 1.6 CFM average air consumption and 6.2 CFM continuous running under load
- Advanced silencing technology reduces noise levels to 75-78 dBA
- Patented double-sealed, lubrication-free motor prevents dust contamination of the air motor and eliminates the need for oiling
- Orbital sanders feature the Universal Tool “smooth design” throttle lever and “ergonomic grip” providing unmatched comfort
- Patented “anti-vibration” motor reduces vibration level to 0.8 m/sec²
- Low weight: Orbital sanders are 2.0 lbs.
- Low profile: Orbital sanders are 4.3” high

Model No.	Description	Pad Size (in)	Orbit (in)	Pad Type	Free Speed (RPM)	Weight (lbs)	Length w/Pad Fitted (in)	Width w/Pad Fitted (in)	Height w/Pad Fitted (in)	Noise Level d(B)A	Vibration m/sec ²	Average Air Cons. (CFM)	Air Inlet NPT/BSP (in.)
UT8789-5-336	5" Orbital Palm Sander	5	3/16	PSA	12,000	2.0	6.7	5.0	4.3	75	0.8	1.6	1/4