



Universal Tool

Air Tools for Industry



UT8896 1/2" DRILL



FEATURES & SPECIFICATIONS

- 0.9 HP Motor for ultimate stall resistance
- Fully caged gears with needle bearings for ultimate reliability
- Ported throttle valve for ultimate control and reliability
- Through handle exhaust with built-in silencing system
- Advanced ergonomically designed handle with "Softouch" coating offers ultimate comfort and reduced vibration
- Jacobs® industrial chuck for accuracy and durability
- Assist handle for added control
- Best for: Continuous drilling in high volume applications

Model #	Motor (hp)	Motor (Kw)	Speed (rpm)	Exhaust	Chuck (in.)	Weight (lb)	Weight (kg)	Length (in)	Length (mm)	Air Inlet (npt)	Rec. Hose (id. in)	Air Cons. (cfm)	Avg. Air Cons. (cfm)
UT8896	0.90	0.66	500	Handle	1/2	3.20	1.5	9.50	241	1/4"	3/8"	18.40	4.60

Recommended Air Pressure of 90 psi - 6.2 bar

Universal Tool, a Division of Florida Pneumatic Manufacturing Corp. • 1660 Silver Beach Road, Suite 100, Lake Park, FL 33403
www.UniversalToolUSA • (800) 356-3392