



**Universal Tool**  
*Air Tools for Industry*



## UT8968 DIRECT DRIVE SCREWDRIVER



### FEATURES & SPECIFICATIONS

- 0.5 HP Motor with direct drive for extra stall resistance
- Unique paddle forward-reverse trigger for instant change in direction
- Compact design for increased access and comfort
- Through handle exhaust
- “Softouch” handle coating offers ultimate comfort and reduced vibration
- Best for: High volume self-tapping assembly

| Model # | Motor (hp) | Motor (Kw) | Torque Range (in. lbs) | Speed (rpm) | Exhaust | Chuck         | Weight (lbs) | Weight (Kg) | Length (in) | Length (mm) | Air Inlet (npt) | Rec. Hose (id. in) | Air Cons. (cfm) | Avg. Air Cons. (cfm) |
|---------|------------|------------|------------------------|-------------|---------|---------------|--------------|-------------|-------------|-------------|-----------------|--------------------|-----------------|----------------------|
| UT8968  | 0.5        | 0.37       | 5-45                   | 1,800       | Handle  | 1/4" Hex Q.C. | 2.25         | 1.00        | 5.0         | 127         | 1/4"            | 3/8"               | 16              | 4.00                 |

Recommended Air Pressure of 90 psi - 6.2 bar