

### FEATURES

- Hard hitting twin hammer-320 ft.lb. max. torque
- Combined reverse and power management switch
- Ergonomic composite housing and grip for lower weight
- Magnesium hammer case for ultimate weight reduction
- Weighs only 2.7 lbs. for reduced operator fatigue
- Best for: Assembly & heavy MRO

### SPECIFICATIONS

|                          |                |
|--------------------------|----------------|
| Square Drive (in.)       | 3/8            |
| Working Torque (ft.-lb.) | 35-205         |
| Working Torque NM        | 48-278         |
| Max. Torque (ft.-lbs.)   | 320            |
| Max Torque (nm)          | 433            |
| Speed (RPM)              | 12,000         |
| Anvil                    | 3/8" Square    |
| Socket Retainer          | Spring Pin     |
| Exhaust                  | Handle         |
| Weight (lbs.)            | 2.7            |
| Weight (kg.)             | 1.3            |
| Length (in.)             | 5.20           |
| Length (mm)              | 132            |
| Air Inlet (in.)          | 1/4            |
| Hose (I.D. in.)          | 3/8            |
| Air Cons. (cfm)          | 20             |
| Avg. Air Cons (cfm)      | 5.0            |
| Rec. Pressure            | 90 psi-6.2 bar |



## Air Tools for Industry

