

FEATURES

- 1.0 HP motor for added stall resistance
- Safety lock-off throttle
- Rear exhaust keeps work area clear of blowing debris
- Ergonomic cushion comfort grip for comfort and reduced vibration
- 260 degree swivel guard and swivel air inlet for ultimate maneuverability in confined work area
- Guard and mounting flanges designed for use with Type 1 wheels
- Total angle head height 2.5"
- Best for: Cutting pipes in boiler installation and repair, petro chemical plant maintenance; as well as cutting bolts and threaded fasteners

SPECIFICATIONS

| | |
|----------------------|----------------|
| Motor (HP) | 1.0 |
| Motor (kW) | 0.73 |
| Max. Wheel Dia. (in) | 4" Type 1 |
| Guard Type | Type 1 |
| Speed (RPM) | 17,000 |
| Exhaust | Rear |
| Collet Size (in) | 3/8"-24 |
| Weight (lbs.) | 3.1 |
| Weight (kg.) | 1.4 |
| Length (in.) | 12.00 |
| Length (mm) | 305 |
| Air Inlet (in.) | 1/4 |
| Rec. Hose (I.D. in.) | 3/8 |
| Air Cons. (cfm) | 20 |
| Avg. Air Cons (cfm) | 5 |
| Rec. Pressure | 90 psi-6.2 bar |



Air Tools for Industry

