

FEATURES

- 2.4 HP governed motor for stall-free operation
- Alloy steel spiral gears with heavy duty bearings for added reliability
- "Rapid-adjust" guard allows rotational adjustment without tools
- Rotational rear-exhaust deflector reduces noise output and allows operator to adjust flow direction
- Compact design - reduced weight
- Spindle lock for rapid wheel change can be moved to right or left side of body
- Vibration damped side handle included
- Insulated composite handle over-mold increases operator comfort

SPECIFICATIONS

| | |
|----------------------|----------------|
| Motor (HP) | 2.4 |
| Motor (kW) | 1.79 |
| Max. Wheel Dia. (in) | 4 |
| Guard Type | Rapid-Adjust |
| Speed (RPM) | 13,500 |
| Exhaust | Rear |
| Spindle Size | 3/8"-24 |
| Weight (lbs.) | 3.6 |
| Weight (kg.) | 1.63 |
| Length (in.) | 9.8 |
| Length (mm) | 248.92 |
| Air Inlet (NPT) | 3/8" |
| Rec. Hose (I.D. in.) | 1/2 |
| Air Cons. (cfm) | 10 |
| Avg. Air Cons (cfm) | 10 |
| Rec. Pressure | 90 psi-6.2 bar |



Air Tools for Industry

