

## FEATURES

- 0.45 HP motor ensures no slow down & clean break through
- Machined carbon fiber blades for lubrication free operation
- Highest precision engineering ensures 600,000 cycles of use
- Internal silencer baffle reduces noise pressure to 81 dBA
- Precision engineered angle head and gears supported by ball bearings; and 1/4" x 28 TPI internal thread
- Angle head interchangeable with UT8893 series
- Best for: Continuous precision air frame work

## SPECIFICATIONS

|                      |                |
|----------------------|----------------|
| Motor (HP)           | 0.45           |
| Motor (kW)           | 0.33           |
| Gear Ratio           | 6:1            |
| Speed (RPM)          | 3,300          |
| Exhaust              | Rear           |
| Chuck (in.)          | 1/4" x 28TPI   |
| Weight (lbs.)        | 1.66           |
| Weight (kg.)         | 0.75           |
| Length (in.)         | 9.75           |
| Length (mm)          | 248            |
| Air Inlet (NPT)      | 1/4            |
| Rec. Hose (I.D. in.) | 3/8"           |
| Air Cons. (cfm)      | 4.0            |
| Avg. Air Cons (cfm)  | 4.0            |
| Rec. Pressure        | 90 psi-6.2 bar |



## Air Tools for Industry

