

FEATURES

- A choice of speeds and hold and drive heads to handle Riv-nut® setting from 3mm to 10mm / 1/4" to 3/8"
- Unique paddle forward-reverse trigger for instant change in direction
- 0.4 HP Motor for extra stall resistance
- Through handle exhaust
- Ergonomic grip offers ultimate comfort and reduced vibration
- A model and head size must be stated when ordering
- Best for: High volume hold and drive applications in aircraft and light assembly industries

SPECIFICATIONS

| | |
|--------------------------------|--------------|
| Motor (HP) | 0.4 |
| Motor (kW) | 0.29 |
| Torque Range (in. lb.) | NA |
| Speed (RPM) | 1,600 |
| Exhaust | Handle |
| Chuck (in.) | N/A |
| Anvil | N/A |
| Head Size and Setting Capacity | 5mm |
| Traction Power | N/A |
| Weight (lbs.) | 2.3 |
| Weight (kg.) | 1.0 |
| Length (in.) | 7.00 |
| Length (mm) | 178 |
| Rec. Pressure | 90psi-6.2bar |
| Rec. Hose (I.D. in.) | 3/8" |
| Air Cons. (cfm) | 4.0 |
| Air Inlet (in.) | 1/4 |



Air Tools for Industry

